



LOWEST OPERATIONAL USE TEMPERATURE (LOUT)

**SafeTemp® ES Plus
Aircraft Deicing Fluid
SAE AMS 1424M Type I**

FOR HIGH-SPEED AIRCRAFT

| | 100/0 | 65/35 | 50/50 |
|-------------------------------------|-----------------|-------------------|-------------------|
| HIGH-SPEED AERODYNAMICS | - | -24.0°F (-31.0°C) | -1.0°F (-18.5°C) |
| FREEZING POINT | Does Not Freeze | -43.0°F (-41.5°C) | -14.8°F (-26.0°C) |
| LOUT FOR HIGH-SPEED AIRCRAFT | DO NOT USE | -24.0°F (-31.0°C) | -1.0°F (-18.5°C) |

FOR LOW-SPEED AIRCRAFT

| | 100/0 | 65/35 | 50/50 |
|------------------------------------|-----------------|-------------------|-------------------|
| HIGH-SPEED AERODYNAMICS | - | -17.5°F (-27.5°C) | -1.0°F (-18.5°C) |
| FREEZING POINT | Does Not Freeze | -43.0°F (-41.5°C) | -14.8°F (-26.0°C) |
| LOUT FOR LOW-SPEED AIRCRAFT | DO NOT USE | -17.5°F (-27.5°C) | -1.0°F (-18.5°C) |

**The data presented is for informational purposes only and shall not constitute a guarantee for any specific product features.*